



## FMT 50 PP LIQUID METER



More than just pumps.

# FLUX FMT 50 PP LIQUID METER



The FMT 50 PP uses an interlocked impeller in the measuring chamber which guarantees fast and safe filling. Suitable for use with low viscosity liquids in conjunction with our JUNIORFLUX & COMBIFLUX pumps, as well as in fixed installations. (Not suitable for use with flammable liquids)

**Benefits:** User-friendly interface for fast and easy calibration. 5-digit LCD-Display allows for easy reading of batch readout, totalizing information and unit of measure.

Type	FMT 50 PP
Flowrate	1.3 - 13.2 GPM (5 - 50 L/min)
Operating pressure at 68°F (20°C)	58 PSIG (4 bar)
Viscosity	40 cPs Max
Operating temperature	14 - 122°F (-10 - 50 °C)
Accuracy (not calibrated)	± 2 %
Accuracy (calibrated)	± 1 %
Inlet-outlet connections*	Inlet G1(1" BSP), Outlet G1A (1" BSP)
Material: housing	Polypropylene (PP)
Material: seal	FKM
Protection	IP65
Weight	0.6 lbs (0.3 kg)
<b>Part No.</b>	<b>A0500003</b>

\* NPT Adapters available

Contact us for more information on FLUX liquid meters, as well as COMBIFLUX & JUNIORFLUX pumps. We will be more than happy to assist with your application and equipment selection.



More than just pumps

## FLUX PUMPS CORPORATION

300 Townpark Drive, Suite 110  
Kennesaw, GA 30144, USA  
Phone 800-367-3589  
info@fluxpumpsusa.com  
www.fluxpumpsusa.com